

imageCLASS
MF469x II
MF465dw II
MF461dw II

Canon
Delighting You Always



A class of *Excellence*

Stay Efficient in a Fast-Paced Business Environment.

Streamline your workflows with the imageCLASS MF460 II Series—engineered for small offices and dynamic workgroups. Whether you're printing a stack of business proposals or digitising original documents, this multifunction printer integrates effortlessly into any workspace. With a space-saving design, wireless connectivity for a clutter-free setup, and an intuitive touchscreen interface, the MF460 II series helps you optimize resources and stay focused on what matters most: growing your business.

UP TO
40 PPM
(A4)
FAST PRINT
SPEED*

QUICK
5.0 SEC
FIRST PRINT
OUT TIME

UP TO
100 IPM
(A4)
DUPLEX
SCAN



MONO
UP TO **10,200**
PAGES
HIGH-YIELD
CARTRIDGE

*Applicable to MF469x II and MF465dw II



INCREASED PRODUCTIVITY

Maximise scanning with the 50-sheet single-pass DADF, using dual CIS to scan both sides at once.



FAVOURITE FUNCTION AT FINGERTIPS

Simplify your workflow with custom shortcuts, an intuitive interface, and a vari-angle touchscreen for faster, more efficient printing.



APPLICATION LIBRARY

BOOST EFFICIENCY / CUSTOMISE WORKFLOW

The Application Library lets you work smarter by storing and printing forms directly, or sending documents to preset destinations with a single tap.



ENHANCED SECURITY FOR A PEACE OF MIND

TLS 1.3 and WPA 3 encrypts data and enhances security for network communications and Wi-Fi connections, respectively. Firmware integrity checks can be done upon startup.

Business Can Be Simple

SPECIFICATIONS / imageCLASS		MF469x II	MF465dw II	MF461dw II
		Print, Scan, Copy, Fax		Print, Scan, Copy
PRINT	Printing Method		Monochrome Laser Beam Printing	
	Print Speed	A4 ¹	40 ppm	36 ppm
		Letter ¹	42 ppm	37 ppm
		2-Sided	33 ipm (A4) / 35 ipm (Letter)	30 ipm (A4) / 31 ipm (Letter)
	Print Resolution		600 x 600 dpi	
	Print Quality with Image Refinement Technology		1,200 x 1,200 dpi (equivalent)	
	Warm-Up Time (From Power On)		14 sec	
	First Print Out Time (FPOT)²	A4	5 sec	
	Print Language		UFR II, PCL 6, Adobe® PostScript® 3™	
	Auto Duplex Print		Yes	
	Print Margins		Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)	
	Supported File Format for USB Direct Print		JPEG, TIFF, PDF	
COPY	Copy Speed	A4	40 ppm	36 ppm
	Copy Resolution		600 x 600 dpi	
	First Copy Out Time (FCOT)	A4	6.1 sec	
	Reduce/Enlargement		25 - 400% in 1% increments	
	Copy Features		Collate 2 on 1, 4 on 1, ID Card Copy, Passport Copy	
	Scan Resolution	Optical	Up to 600 x 600 dpi	
		Driver Enhanced	Up to 9,600 x 9,600 dpi	
	Scan Type		Colour Contact Image Sensor	
	Maximum Scan Size	Platen Glass	Up to 216 x 297 mm	
		ADF	Up to 216 x 356 mm	
Scan Speed³	Platen Glass	1.8/1.9 sec (mono/colour)		
	ADF	1-Sided: 50 ipm (mono) / 40 ipm (colour) 2-Sided: 100 ipm (mono) / 80 ipm (colour)		
Colour Depth		24-bit		
Pull Scan		Yes, USB and Network		
Push Scan (Scan To PC) with MF Scan Utility		Yes, USB and Network		
Scan To Cloud		MF Scan Utility		
Scan Driver Compatibility		TWIN, WIA		
SEND Method		SMB, Email, FTP, iFAX Simple	SMB, Email, FTP	
SEND	Colour Mode		Full Colour, Greyscale, Monochrome	
	Scan Resolution		300 x 600 dpi	
	File Format		JPEG, TIFF, PDF, Compact PDF, PDF (OCR)	
FAX	Modem Speed		Up to 33.6 Kbps (Up to 3 sec/page)	-
	Fax Resolution		Up to 400 x 400 dpi	
	Compression Method		MH, MR, MMR, JBIG	
	Memory Capacity⁴		Up to 90 jobs	
	Speed Dials		Up to 281 dials	
	Group Dials / Destinations		Max. 299 dials / Max. 50 destinations in one group	
	Sequential Broadcast		Max. 310 destinations	
	Receive Mode		Fax Only, Fax/Tel Auto Switch, Answer Mode, Manual	
	Memory Backup		Permanent Fax Memory Backup	
	Fax Features		Fax Forwarding, Remote Reception, PC Fax (Transmit Only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports	

¹ Print speed is measured based on internal testing using A4/Letter size paper printed with 100% print ratio to original on one-sided paper.

Internal testing involved continuously printing the same one page of content on plain paper. Print speed may vary depending on paper type, paper size or paper feeding direction.

² First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.

³ Scan resolution 300 x 300 dpi.

⁴ Based on ITU-T #1 Chart (standard mode).

⁵ The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from the <https://asia.canon/en/support> website when available.

⁶ Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

⁷ Excluding toner cartridge.

⁸ Toner cartridge yield is in accordance with ISO/IEC 19752.

SPECIFICATIONS / imageCLASS		MF469x II	MF465dw II	MF461dw II	
		Print, Scan, Copy, Fax		Print, Scan, Copy	
PAPER HANDLING	Input Tray Capacity (Plain Paper, 80 g/m²)	Standard	Cassette	250 sheets	
		Standard	Multi Purpose Tray	100 sheets	
		Standard	ADF	50 sheets Duplex, Single Pass	
		Optional	Paper Feeder	550 sheets	
		Optional	Maximum	900 sheets (Cassette + 1 Paper Feeder)	
	Output Tray Capacity (Plain Paper, 80 g/m²)		150 sheets		
	Media Size	Cassette/Paper Feeder	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Custom (min. 105 x 148 mm to max. 216 x 355.6 mm)		
		Multi Purpose Tray	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Index Card, Postcard, Envelope (COM10, Monarch, DL, C5), Custom (min. 76.2 x 127 mm to max. 216 x 355.6 mm)		
		ADF	A4, A5, Letter, Legal (min. 148 x 105 mm to max. 216 x 356 mm), Business Card: 48 x 85 mm		
		2-Sided Printing	A4, Legal, Letter, Foolscap, Indian Legal, Custom (min. 210 x 279.4 mm to max. 216 x 355.6 mm)		
	Media type		Plain Paper, Recycled paper, Colour Paper, Bond Paper		
	Media Weight	Cassette/Paper Feeder	60–120 g/m ²		
Multi Purpose Tray		60–199 g/m ²			
ADF		50 – 105 g/m ² (Business Card: 80 to 209 g/m ²)			
Standard Interface	Wired	USB 2.0, 10Base-T/100Base-TX/1000Base-T			
	Wireless	Wi-Fi 802.11b/g/n (Infrastructure Mode, Access Point, WPS)			
Network Protocol	Print	LPD, RAW, IPP, IPPS, WSD-Print (IPv4, IPv6)			
	Scan	Email, SMB, WSD-Scan (IPv4, IPv6), FTP, Oauth 2.0			
	TCP/IP Application Services	mDNS, DHCP, Auto IP (IPv4), DHCPv6 (IPv6)			
	Management	SNMPv3 (IPv4, IPv6), HTTP/HTTPS, SNTIP			
Network Security	Wired	IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE802.1X, IPsec, TLS 1.3			
	Wireless	Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE(AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE(AES)			
Mobile Solution		Canon PRINT app, AirPrint®, Mopria® Print Service, Microsoft Universal Print			
Compatible Operating Systems⁵		Windows® 10/11, Windows® Server 2016/2019/2022/2025, macOS 10.15 or later, Linux, Chrome OS			
Other Features		Department ID, Secure Print, Skip Blank Page, Application Library			
Available Software		Printer Driver, Fax Driver, Scanner Driver, MF Scan Utility, Toner Status	Printer Driver, Scanner Driver, MF Scan Utility, Toner Status		
Device Memory		1 GB			
Storage (eMMC)		2 GB			
Display		5" LCD Touchscreen			
Power Requirements		AC 220 – 240 V, 50/60 Hz			
Power Consumption (Approx.)	Operation	480 W (max. 1,280 W)			
	Standby	6 W			
	Sleep	0.9 W			
Operating Environment	Temperature	10 – 30°C			
	Humidity	20 – 80% RH (no condensation)			
Monthly Duty Cycle⁶		80,000 pages			
Dimensions (W x D x H)		420 x 460 x 375 mm			
Weight⁷		16.2 kg			
Toner Cartridge⁸	Standard	Cartridge 070: 3,000 pages (Bundled: 3,000 pages)			
	High	Cartridge 070H: 10,200 pages			
Paper Feeder		Cassette Feeding Unit-AH1 (550 sheets)			
Barcode Printing		Barcode Printing Kit-E1E	-		



Delighting You Always

**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.**

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522
Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.