

SPEED AND CONNECTIVITY *WITHOUT COMPROMISE*



imageFORCE 710 series brings together high-speed output, advanced connectivity, and a streamlined design tailored for modern workplaces.

Delivering speeds up to 71 ppm, the 710 Series keeps pace with demanding office tasks while Wi-Fi 6 connectivity brings faster, more reliable wireless performance for effortless integration.

Built for enterprise-level security, imageFORCE 710 Series offers FIPS 140-3 compliance and security environment estimation to help organisations strengthen device protection by recommending optimal configurations and minimising potential risks.



CONNECTIVITY

Get the option to access cloud platforms like Google Drive and Dropbox directly from the device. Enjoy mobile printing with Canon PRINT, Apple AirPrint and more for ultimate convenience.



SECURITY

Advanced protection for your data, with features like user authentication and audit logs that help you monitor and mitigate potential risks.



RELIABILITY

Engineered for optimal performance, with intelligent maintenance tools and long-lasting parts that reduce downtime and maximise uptime.



SUSTAINABILITY

Built with up to 20% recycled plastic, supported by eco-friendly packaging and lower energy consumption.

imageFORCE 710 Specifications

Main Unit

Machine type

A4 Monochrome Laser Multifunctional

Core functions

Print, Copy, Scan, Send, Store and optional Fax

Processor

Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Colour Touch panel

Memory

RAM: 4.5GB

Storage

SSD (Standard): 256GB

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T
Optional: Wireless LAN (IEEE 802.11a/b/g/n/ac/ax)

Others

Standard: USB 2.0 x 1 (Host), USB 3.0 x 1 (Host),
USB 2.0 x 1 (Device)
Optional: Serial Interface, Copy Control
Interface

Paper Supply Capacity (A4, 80gsm)

Standard: 650 sheets
100-sheet Multi-purpose tray
550-sheet Paper cassette x 1
Maximum: 3,200 sheets (with High Capacity
Cassette Feeding Unit-D1)

Paper output capacity (A4, 80gsm)

500 sheets

Supported Media Types

Multi-purpose tray:

Thin, Plain, Recycled, Colour, Heavy, Bond,
Transparency, Letterhead, Envelope

Paper Cassette:

Thin, Plain, Recycled, Colour, Heavy, Bond,
Label, Pre-Punched, Letterhead

Supported Media Sizes

Multi-purpose tray:

Standard size: A4, A5, A5R, A6, B5
Custom size: 76.2 x 127.0 mm to 216.0 x 355.6
mm
Envelopes: COM10 No.10, Monarch, DL, ISO-C5

Paper Cassette:

Standard size: A4, A5, A5R, A6, B5
Custom size: 99.0 x 148.0 mm to 216.0 x 297.0
mm

Supported media weights

Multi-purpose tray: 60 to 200 gsm
Paper Cassette: 60 to 135 gsm
Duplex: 60 to 120 gsm

Warm-up Time

Quick Startup Mode: 4 seconds or less*
* Time from device power-on to when the copy icon
appears and is enabled to operate on the touch panel
display.

From Power On: 10 seconds or less*

* Time from device power-on, until copy ready
(not print reservation)

From Sleep Mode: 10 seconds or less

Dimensions (W x D x H)

500 x 598 x 617 mm

Installation Space(W x D)

1,052 x 823 mm (with left Ink cartridge door
open + right door open + the cassette drawer
open)

Weight*

*including regular toner
Approx. 36kg including toner

Print Specifications

Print Speed*

imageFORCE 710
Up to 71 ppm (A4), Up to 113 ppm (A5),
Up to 40 ppm (A5R, A6)
imageFORCE 610
Up to 61 ppm (A4), Up to 99 ppm (A5),
Up to 35 ppm (A5R, A6)
imageFORCE 520
Up to 52 ppm (A4), Up to 80 ppm (A5),
Up to 35 ppm (A5R, A6)
* 1-sided

Print Resolution (dpi)

1,200 x 600
(*Data processing is 2,400 equivalent x 600, 1,200 x 1,200 equivalent)

Page description languages

Standard: UFR II, PCL6/PCL5, Adobe PostScript 3

Direct Print

Supported file types: PDF, EPS, TIFF/JPEG, and XPS

Printing from mobile and cloud

AirPrint, Mopria, IPP Everywhere, Canon PRINT,
uniFLOW Online, Universal Print and Cloud
Connector

OS Standard Printing

Android *1, Windows® 11 *1, Chrome OS *1, macOS
(11.2.2 or later) *2, iOS (15.2 or later) *2, iPadOS *2
*1 Need to select the [Use Mopria] check box [OK]
*2 Need to select the [Use AirPrint] check box [OK]

Fonts

PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T*1 (Japanese, Korean,
Simplified and Traditional Chinese), Barcode fonts*2
*1 Optional PCL International Font Set-A1 is required.
*2 Optional Barcode Printing Kit-D1 is required.

Operating System

UFR II:
Windows®11/Server2016/Server2019/
Server2022/Server2025, macOS (10.14 or later)
PCL:
Windows®11/Server2016/Server2019/
Server2022/Server2025
PS:
Windows®11/Server2016/Server2019/
Server2022/Server2025, macOS (10.14 or later)
PPD: Windows® 11, macOS (10.15 or later)

As of Dec. 2024

Copy Specifications

Copy Speed

imageFORCE 710
Up to 71 ppm (A4), Up to 113 ppm (A5),
Up to 40 ppm (A5R, A6)
imageFORCE 610
Up to 61 ppm (A4), Up to 99 ppm (A5),
Up to 35 ppm (A5R, A6)
imageFORCE 520
Up to 52 ppm (A4), Up to 80 ppm (A5),
Up to 35 ppm (A5R, A6)
* 1-sided

First-Copy-Out Time (A4)

Approx. 5 seconds or less

Copy resolution (dpi)

600 x 600

Multiple Copies

Up to 9,999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25% to 400% (1% Increments)

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)]

* Multi-Sheet Feed Detection is supported.

Document Feeder Paper Capacity (80 gsm)

up to 100 Sheets

Document Feeder acceptable paper weight

Document Feeder media weight:

1-sided scanning: 42 to 128 gsm (BW), 64 to 128 gsm (CL)

2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)

Note:

Business card: 80 to 220 gsm

Original width narrower than A6 except business card: 50 to 128 gsm

Long Original(over than 355.6mm): 60 to 90gsm

Supported media sizes

Platen scanning size: up to 216.0 x 355.6 mm

Document Feeder media size:

A4, A5R, A6, B5

Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm

Business card: 48.0 x 85.0 mm to 55.0 x 91.0 mm

Scan Speed (ipm: A4)

Send (300 x 300 dpi):

Automatic Colour Select "OFF":

1-sided Scanning: 95

2-sided Scanning: 190

Automatic Colour Select "ON":

1-sided Scanning: 50

2-sided Scanning: 100

Copy:

Scan Speed Priority (300x600dpi: default)

1-sided Scanning: 95

2-sided Scanning: 140

Scan Resolution (dpi)

600x600

Pull Scan Specifications

Colour Network ScanGear2. For both TWAIN and WIA

Supported OS: Windows® 10/11/Server

2016/Server 2019/Server 2022/Server 2025

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP*), SMB, FTP, WebDAV, Mail Box

Optional: Super G3 FAX, IP Fax

* Available OAuth 2.0 authentication method on Microsoft 365 and Google Workspace

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Communication protocol

File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3

File Format

TIFF, JPEG, PDF (Compact, Searchable, Optimize for Web, PDF A/1-b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines

1

Modem Speed

Super G3: 33.6 kbps

G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)

Sending/Receiving Size

Sending: A4, A5R*, A6*, B5*

Receiving: A4, A5*, A5R, B5

* Sent as A4

FAX memory

Up to 30,000 pages (2,000 jobs)

Speed dials

Max. 200

Group dials/destinations

Max. 199 dials

Sequential broadcast

Max. 256 addresses

Memory backup

Yes

Store Specifications

Mail Box (Number supported)

100 User Inboxes,

1 Memory RX Inbox,

50 Confidential Fax Inboxes

Maximum 30,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported Client PC: Windows® 11

Concurrent Connections (Max.): SMB:64,

WebDAV:3

Advanced Box available disc space

Standard: 16 GB

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH

(Relative Humidity/No condensation)

Power source

220-240 V, 50/60 Hz, 4.8 A

Power consumption

Maximum: Approx. 1,500 W

Sleep mode: Approx. 0.36 W*

* 0.36 W sleep mode is not available in all circumstances due to certain settings.

Consumables

Toner Cartridges

T03 Black

Toner Yield

51,500 *(A4)

* Toner cartridge yield in accordance with ISO/IEC 19752

Configuration Output Options*



/ Cassette Feeding Unit-AR1

- Supports up to A4
- Media Weight 60-135 gsm
- 550 sheets (80 gsm)
- Floor standing



/ Cassette Feeding Unit-AX1

- Supports up to A4
- Media Weight 60-135 gsm
- 3 x 550 sheets (80 gsm)
- Floor standing



/ High Capacity Cassette Feeding Unit-D1

- Supports up to A4
- Media Weight 60-135 gsm
- 1 x 550 sheets (80 gsm)
- 1 x 2,000 sheets (80 gsm)
- Floor standing



/ Cassette Module-AG1

- Supports up to A4
- Media Weight 60-135 gsm
- 550 sheets (80 gsm)
- Desktop



/ Envelope Cassette-A1

- Media Weight 80 to 100 gsm
- 75 Sheets (Envelope)
- Desktop

*Paper capacity may vary with different paper type/size.



Partner / Dealer Stamp

To arrange for a demonstration, simply contact our office below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #14-10 Galaxis Singapore 138522
Tel: 65-6799 8888 | Fax: 65-6799-8882 | <https://asia.canon/> | <https://sg.canon/>

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageFORCE, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "eMaintenance" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pte Ltd.

Adobe, LiveCycle, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2025 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore.